

# Accessories & Parts

## 116.585.00.1

### Product Type

---

Commander™ Handheld Programming Unit

### Features & Specifications

---

- Commander™ handheld programming unit maintains and monitors your faucets. Adjust faucet run-time and change between five preset running modes, including Hygiene Flush.
- Touch screen operation, powered by 2 'AA' batteries (included)
- Pre-loaded software, ready to use
- For 2-way communication with HyTronic®, E-Tronic®, ELR, EVR, and 8453 Series electronic faucets
- Infrared communication with faucets; micro USB for connection to PC
- Track faucet usage with data export capability
- Complies with the requirements of the Buy American Act of 1933.
- CFNow! Item Ships in 3 Days

### Warranty

---

- 1-Year Limited Material Warranty

### Codes & Standards

---

Job Name \_\_\_\_\_

Item Number \_\_\_\_\_

Section/Tag \_\_\_\_\_

Model Specified \_\_\_\_\_

Architect \_\_\_\_\_

Engineer \_\_\_\_\_

Contractor \_\_\_\_\_


Submitted as Shown       Submitted with Variations

Date \_\_\_\_\_



**Architect/Engineer Specification**

Chicago Faucets No. 116.585.00.1, Commander™ Handheld Programming Unit. For 2-way Communication with HyTronic®, E-Tronic® 40, E-Tronic® 80, ELR, EVR, and 8453 Series electronic faucets. Color touch screen. Infrared communication with faucets; micro USB for connection to PC. Pre-loaded software, ready to use. Allows operator to adjust faucet run-time, change between preset running modes, and track faucet usage by downloading data from the faucet to the handheld unit. Screen size: 3.3 inches. Dimensions: 3.1 x 4.8 x 1.3. Weight: 7.3 oz. Powered by 2 'AA' batteries (included).



**Operation and Maintenance**

Installation should be in accordance with local plumbing codes. Flush all pipes thoroughly before installation. After installation, remove spout outlet or flow control and flush faucet thoroughly to clear any debris. Care should be taken when cleaning the product. Do not use abrasive cleaners, chemicals or solvents as they can result in surface damage. Use mild soap and warm water for cleaning and protecting the life of Chicago Faucet products. For specific operation and maintenance refer to the installation instructions and repair parts documents that are located at [www.chicagofaucets.com](http://www.chicagofaucets.com).

Chicago Faucets, member of the Geberit Group, is the leading brand of commercial faucets and fittings in the United States, offering a complete range of products for schools, laboratories, hospitals, office buildings, food service, airports and sport facilities. Call 1.800.TECTRUE or 1.847.803.5000 Option 1 for installation or other technical assistance.

