

HyTronic® Traditional

- 5-5/8" Height to Outlet
- 0.35 GPM (1.3 L/min) Vandal Proof Outlet



Power Source				Model		
DC	AC	AC EBPS	None	Concealed	User Adjustable	Number
•	_	_	•	_	_	116.201.AB.4
•	_	_	_	•	_	116.211.AB.4
	-	_	=	-	•	116.221.AB.4
_	•	_		_	_	116.101.AB.4
_	•	_	-	•	-	116.111.AB.4
_	•	_	_	_	•	116.121.AB.4
_	_	•		_	_	116.661.AB.1
_	-	•	_	•	-	116.662.AB.1
_	_		_	_	•	116.663.AB.1

HyTronic® Contemporary

- 6-1/8" Height to Outlet
- 0.35 GPM (1.3 L/min) Vandal Proof Outlet



Power Source		Mixer			Model	
DC	AC	AC EBPS	None	Concealed	User Adjustable	Number
•	_	_	•	_	_	116.202.AB.4
•	_	_	_	•	_	116.212.AB.4
	_	_	_	_	•	116.222.AB.4
_	•	-	•	_	_	116.102.AB.4
_	•	_	_		-	116.112.AB.4
_	•	_	_	_	•	116.122.AB.4
-	-		•	-	-	116.664.AB.1
_	_		_		_	116.665.AB.1
_	_		-	-	•	116.666.AB.1

HyTronic® Curve

- 7-1/4" Height to Outlet
- 0.35 GPM (1.3 L/min) Vandal Proof Outlet
- Laminar Flow Models Available



Power Source		Mixer			Model	
DC	AC	AC EBPS	None	Concealed	User Adjustable	Number
•	_	_	•	_	_	116.857.AB.4
•	_	_	_		_	116.867.AB.4
•	_	_	_	_	•	116.877.AB.4
•	-	_	=		_	116.869.AB.4*
•	_	_	_	_	•	116.879.AB.4*
-	•	-		-	-	116.757.AB.4
_	•	_	_	•	_	116.767.AB.4
_	•	_	_	-	•	116.777.AB.4
_	_	•		_	_	116.667.AB.1
_	_	•	=		_	116.767.AB.1
_	_	•	_	_	•	116.669.AB.1
_	_	•	_	_	_	116.670.AB.1*
_	_	•	_	•	_	116.671.AB.1*
_		•	_	_	•	116.672.AB.1*