

# Accessories & Parts

## 131-NF

### Product Type

---

Thermostatic mixing valve for single or multiple faucet installations

### Features & Specifications

---

- Adjustment cap with locking feature
- Brass body construction with corrosion-resistant internal components, includes plastic wall bracket
- Standard 3/8" compression Inlet and outlet
- Integral inlet check valves to protect against cross-flow
- CFNow! Item Ships in 3 Days

### Warranty

---

- 1-Year Limited Cartridge Warranty
- Lifetime Limited Faucet Warranty
- 1-Year Limited Finish Warranty
- 1-Year Limited Material Warranty

### Codes & Standards

---

-  ASSE 1070/ASME A112.1070/CSA B125.70

Job Name \_\_\_\_\_

Item Number \_\_\_\_\_

Section/Tag \_\_\_\_\_

Model Specified \_\_\_\_\_

Architect \_\_\_\_\_

Engineer \_\_\_\_\_

Contractor \_\_\_\_\_


Submitted as Shown       Submitted with Variations

Date \_\_\_\_\_

*No  
Image  
Available*

**Architect/Engineer Specification**

Chicago Faucets No. 131-NF, Thermostatic Mixing Valve. Standard 3/8 compression inlet and outlet. Integral inlet check valves to protect against cross-flow. Adjustment cap with locking feature. Brass Body Construction. Corrosion resistant internal components. Thermostatic Wax Element Design. Thermostat controls both hot and cold water. Installs between the stop valves and the faucet. Single use or multiple faucet installations. Minimum supply pressure: 30psi (207 kPa); Hot inlet temperature: 100F-180F (38C-82). Outlet water temperature will be less than hot water inlet temperature. Includes wall bracket. Minimum flow rate: 0.5 gpm (@ min. 10 psi). Maximum flow rate: 6.4 gpm (@ min. 120 psi). Temperature out: 80F to 120F (27C to 49C).



**Operation and Maintenance**

Installation should be in accordance with local plumbing codes. Flush all pipes thoroughly before installation. After installation, remove spout outlet or flow control and flush faucet thoroughly to clear any debris. Care should be taken when cleaning the product. Do not use abrasive cleaners, chemicals or solvents as they can result in surface damage. Use mild soap and warm water for cleaning and protecting the life of Chicago Faucet products. For specific operation and maintenance refer to the installation instructions and repair parts documents that are located at [www.chicagofaucets.com](http://www.chicagofaucets.com).

Chicago Faucets, member of the Geberit Group, is the leading brand of commercial faucets and fittings in the United States, offering a complete range of products for schools, laboratories, hospitals, office buildings, food service, airports and sport facilities. Call 1.800.TECTRUE or 1.847.803.5000 Option 1 for installation or other technical assistance.



2100 South Clearwater Drive  
Des Plaines, IL  
P: 847/803-5000  
F: 847/803-5454  
Technical: 800/TEC-TRUE  
[www.chicagofaucets.com](http://www.chicagofaucets.com)